

HULK L-4 / L-5



The Hulk has a unique tread pattern that allows it to operate in severe applications while providing superior self cleaning characteristics. The Hulk has a minimum tread depth of 44/32nds and a lug to void ratio of 68% solid to 32% void. Because of the deep tread depth and solid to void ratio, the Hulk L-5 will provide extraordinary hours of service and reduces downtime due to cuts and punctures.

APPLICATIONS

- Skid Steer
- Mining
- Front Backhoe
- Rear Backhoe

SIZE	TYPE	PR	RIM	WT.	N.S.	OD/SW	SLR	C.C.	A.P.	SP.	CODE
10-16.5 L-5	TL	10	8.25	79	44	31.7/10.2	14.4	3,500	40	5	133260
12-16.5 L-5	TL	12	9.75	96	44	32.9/12.0	15.1	4,210	40	5	133266
33/15.50-16.5 L-5	TL	14	12.00	117	44	33.1/15.1	15.1	4,830	35	5	133273
14-17.5 L-5	TL	14	10.50	130	46	36.0/13.8	16.5	5,260	35	5	133278
16.9-24 L-4	TL	12	15.00	276	48	51.0/16.8	23.8	7,150	38	25	202432
19.5L-24 L-4	TL	14	16.00	310	48	52.1/19.3	23.9	8,250	38	25	202440