Grand L40 Series

Kubota

SPECIFICATIONS

Specifications

Model		L3240				
		F (2WD)	DT (4WD)	GST (4WD)	HST (4WD)	HSTC (4WD, CAB)
Engine						
Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel				
Engine gross power	HP (kW)	34.0 (25.4)				
Engine net power	HP (kW)	32.0 (23.9)				
PTO power	HP (kW)	26.5 (19.8)			25.0 (18.7)	
No. of cylinders / Aspiration		3 / Natural				
Bore & stroke	in. (mm)	3.4 × 3.6 (87 × 92.4)				
Total displacement	cu. in. (cc)	100.5 (1647)				
Rated speed	rpm	2700				
Battery		12V, RC: 123 min, CCA: 490A				
Alternater		12V, 40A				12V, 60A
Fuel tank capacity	US gal. (ℓ)	11.6 (44)				
PTO						
Rear PTO Revolution		1 speed: 540 rpm				
Type		Independent			Independent*1	
Mid PTO		Option				
Revolution		1 speed: 2000 rpm				
Hydraulic						
Lift control type: Position		Standard				
Draft		Option				
Implement pump	GPM (ℓ/min.)	8.3 (31.5)				
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)				
Total hydraulic flow	GPM (ℓ/min.)	13.2 (50.1)				
3-point hitch		Category I				
Lift capacity at 24 in. behind lift point	lbs. (kg)	2646 (1200)				
Traveling System						
Transmission		FST 8F/8R		GST 12F/8R	HST Plus (3 Ranges)	
Steering		Hydrostatic power steering				
Brake		Wet disc type				
Clutch		Dry type single stage				
Standard tire size*2	Front	6.0-16	7.2-16			
	Rear	12.4-24				

Travel speeds			GST*3		HST Plus		
No. of speeds (at rated engine speed)			12 Forward /8 Reverse				
			Forward	Reverse		Forward	Reverse
First	Ninth	mph (km/h)	1.0 (1.6) 5.7 (9.2)	0.9 (1.5)	H-DS L	L: 2.2 (3.5)	L: 1.9 (3.1)
Second	Tenth		1.4 (2.3) 6.9 (11.1)	1.4 (2.2)		M: 4.4 (7.1)	M: 4.0 (6.4)
Third	Eleventh		1.9 (3.1) 11.2 (18.0)	2.2 (3.5)		H: 9.4 (15.1)	H: 8.5 (13.6)
Fourth	Twelfth		2.3 (3.7) 16.5 (26.6)	3.2 (5.2)			
Fifth			2.8 (4.5)	4.7 (7.5)	H-DS H	L: 3.6 (5.8)	L: 3.3 (5.3)
Sixth			3.4 (5.4)	6.6 (10.6)		M: 7.4 (11.9)	M: 6.2 (10.7)
Seventh			4.0 (6.5)	10.7 (17.2)		H:15.7 (25.3)	H:14.2 (22.8)
Eighth			4.8 (7.8)	15.8 (25.4)			

Dimensions							
Overall length (w/o 3P)		in. (mm)	119.3 (3030)	115.0 (2920)			
Overall width (min. tread)		in. (mm)	59.8 (1520)				
Overall height (w/Foldable ROPS)		in. (mm)	94.0 (2390)				89.6 (2275)
Wheelbase		in. (mm)	71.3 (1810)	71.1 (1805)			
Min. ground clearance		in. (mm)	14.0 (355)				
Tread	Front	(Front tire) in. (mm)	47.6 (1210) 51.6 (1310) 55.5 (1410) 59.4 (1510)	45.5 (1155)			
	Rear	(Rear tire) in. (mm)	47.2 (1200) 51.2 (1300) 54.5 (1385) 58.3 (1480)				
Min. turning radius (w/brake, 4WD disengaged)		feet (m)	8.5 (2.6)	8.9 (2.7)			
Weight (with ROPS)		lbs. (kg)	3153 (1430)	3252 (1475)	3296 (1495)	3395 (1540)	3748 (1700)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.
For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. Not for sale in Nebraska.
*1 With Master Clutch. *2 Kubota offers several tire options. *3 Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.*

Grand L40 Series

Kubota

SPECIFICATIONS

Specifications

Model		L3540		
		GST (4WD)	HST (4WD)	HSTC (4WD, CAB)
Engine				
Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel		
Engine gross power	HP (kW)	37.0 (27.6)		
Engine net power	HP (kW)	35.0 (26.1)		
PTO power	HP (kW)	29.5 (22.0)	28.0 (20.9)	
No. of cylinders / Aspiration		3 / Natural		
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)		
Total displacement	cu. in. (cc)	111.4 (1826)		
Rated speed	rpm	2700		
Battery		12V, RC: 133 min, CCA: 582A		
Alternater		12V, 40A		12V, 60A
Fuel tank capacity	US gal. (ℓ)	11.6 (44)		
PTO				
Rear PTO Revolution		1 speed: 540 rpm		
Type		Independent	Independent *1	
Mid PTO		Option		
Revolution		1 speed: 2000 rpm		
Hydraulic				
Lift control type: Position		Standard		
Draft		Option		
Implement pump	GPM (ℓ/min.)	8.3 (31.5)		
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)		
Total hydraulic flow	GPM (ℓ/min.)	13.2 (50.1)		
3-point hitch		Category I		
Lift capacity at 24 in. behind lift point	lbs. (kg)	2650 (1200)		
Traveling System				
Transmission		GST 12F/8R	HST Plus (3 Ranges)	
Steering		Hydrostatic power steering		
Brake		Wet disc type		
Clutch		Dry type single stage		
Standard tire size *2	Front	7.2-16		
	Rear	12.4-24		

Travel speeds

No. of speeds (at rated engine speed)			GST *3 12 Forward /8 Reverse			HST Plus		
			Forward		Reverse		Forward	Reverse
First	Ninth	mph (km/h)	1.0 (1.6)	5.7 (9.2)	0.9 (1.5)	H-DS L	L: 2.2 (3.5)	L: 1.9 (3.1)
Second	Tenth		1.4 (2.3)	6.9 (11.1)	1.4 (2.2)		M: 4.4 (7.1)	M: 4.0 (6.4)
Third	Eleventh		1.9 (3.1)	11.2 (18.0)	2.2 (3.5)		H: 9.4 (15.1)	H: 8.5 (13.6)
Fourth	Twelfth		2.3 (3.7)	16.5 (26.6)	3.2 (5.2)			
Fifth			2.8 (4.5)		4.7 (7.5)	H-DS H	L: 3.6 (5.8)	L: 3.3 (5.3)
Sixth			3.4 (5.5)		6.6 (10.6)		M: 7.4 (11.9)	M: 6.2 (10.7)
Seventh			4.0 (6.5)		10.7 (17.2)		H:15.7 (25.3)	H:14.2 (22.8)
Eighth			4.8 (7.8)		15.8 (25.4)			

Dimensions				
Overall length (w/o 3P)	in. (mm)	115.0 (2920)		
Overall width (min. tread)	in. (mm)	59.8 (1520)		
Overall height (w/Foldable ROPS)	in. (mm)	94.0 (2390)		89.6 (2275)
Wheelbase	in. (mm)	71.1 (1805)		
Min. ground clearance	in. (mm)	14.0 (355)		
Tread Front	(Front tire) in. (mm)	45.5 (1155)		
Rear	(Rear tire) in. (mm)	47.2 (1200) 51.2 (1300) 54.5 (1385) 58.3 (1480)		
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)		
Weight (with ROPS)	lbs. (kg)	3296 (1495)	3395 (1540)	3748 (1700)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. Not for sale in Nebraska.
*[*1] With Master Clutch. [*2] Kubota offers several tire options. [*3] Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.*

Grand L40 Series

Kubota

SPECIFICATIONS

Specifications

Model		L3940			
		DT (4WD)	GST (4WD)	HST (4WD)	HSTC (4WD, CAB)
Engine					
Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel			
Engine gross power	HP (kW)	40.5 (30.2)			
Engine net power	HP (kW)	38.5 (28.7)			
PTO power	HP (kW)	33.0 (24.6)		31.5 (23.5)	
No. of cylinders / Aspiration		4 / Natural			
Bore & stroke	in. (mm)	3.3 × 3.6 (83 × 92.4)			
Total displacement	cu. in. (cc)	122.0 (1999)			
Rated speed	rpm	2700			
Battery		12V, RC: 133 min, 582A			
Alternater		12V, 40A			12V, 60A
Fuel tank capacity	US gal. (ℓ)	13.2 (50)			
PTO					
Rear PTO					
Revolution		1 speed: 540 rpm			
Type		Independent		Independent*1	
Mid PTO		Option			
Revolution		1 speed: 2000 rpm			
Hydraulic					
Lift control type: Position		Standard			
Draft		Option			
Implement pump	GPM (ℓ/min.)	9.8 (37.0)			
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)			
Total hydraulic flow	GPM (ℓ/min.)	14.7 (55.6)			
3-point hitch		Category I			
Lift capacity at 24 in. behind lift point	lbs. (kg)	2760 (1250)			
Traveling System					
Transmission		FST 8F/8R	GST 12F/8R	HST Plus (3 Ranges)	
Steering		Hydrostatic power steering			
Brake		Wet disc type			
Clutch		Dry type single stage			
Standard tire size*2	Front	8.3-16			
	Rear	14.9-24			

Travel speeds

No. of speeds (at rated engine speed)

			GST*3 12 Forward /8 Reverse		HST Plus		
			Forward	Reverse		Forward	Reverse
First	Ninth	mph (km/h)	0.9 (1.5)	5.5 (8.9)			
Second	Tenth		1.3 (2.2)	6.6 (10.7)			
Third	Eleventh		1.8 (2.9)	10.8 (17.4)			
Fourth	Twelfth		2.2 (3.5)	16.0 (25.7)			
Fifth			2.6 (4.2)		0.9 (1.5)	H-DS L	L: 2.2 (3.6) L: 2.0 (3.2)
Sixth			3.2 (5.1)		1.2 (2.2)		M: 4.5 (7.3) M: 4.0 (6.5)
Seventh			3.9 (6.3)		2.1 (3.3)		H: 9.6 (15.4) H: 8.6 (13.9)
Eighth			4.7 (7.6)		3.0 (4.9)		
					4.5 (7.2)	H-DS H	L: 3.7 (5.9) L: 3.4 (5.4)
					6.3 (10.2)		M: 7.5 (12.1) M: 6.8 (10.9)
					10.3 (16.6)		H:16.0 (25.8) H:14.4 (23.2)
					15.2 (24.5)		

Dimensions					
Overall length (w/o 3P)	in. (mm)	121.5 (3085)			
Overall width (min. tread)	in. (mm)	66.5 (1690)			
Overall height (w/Foldable ROPS)	in. (mm)	94.4 (2400)			90.2 (2290)
Wheelbase	in. (mm)	74.6 (1895)			
Min. ground clearance	in. (mm)	14.6 (370)			
Tread Front	(Front tire) in. (mm)	45.5 (1155)			
Rear	(Rear tire) in. (mm)	50.6 (1285) 56.5 (1435) 60.2 (1530)			
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)			
Weight (with ROPS)	lbs. (kg)	3483 (1580)	3527 (1600)	3627 (1645)	3968 (1800)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.
For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. Not for sale in Nebraska.
**1 With Master Clutch. *2 Kubota offers several tire options. *3 Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.*

Grand L40 Series

Kubota

SPECIFICATIONS

Specifications

Model		L4240			
		DT (4WD)	GST (4WD)	HST (4WD)	HSTC (4WD, CAB)
Engine					
Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel			
Engine gross power	HP (kW)	44.0 (32.8)			
Engine net power	HP (kW)	42.0 (31.3)			
PTO power	HP (kW)	36.5 (27.2)		35.0 (26.1)	
No. of cylinders / Aspiration		4 / Natural			
Bore & stroke	in. (mm)	3.4 × 3.6 (87 × 92.4)			
Total displacement	cu. in. (cc)	134.1 (2197)			
Rated speed	rpm	2700			
Battery		12V, RC: 133 min, 582A			
Alternater		12V, 40A			
Fuel tank capacity	US gal. (ℓ)	13.2 (50)			
PTO					
Rear PTO Revolution		1 speed: 540 rpm			
Type		Independent		Independent *1	
Mid PTO		Option			
Revolution		1 speed: 2000 rpm			
Hydraulic					
Lift control type: Position		Standard			
Draft		Option			
Implement pump	GPM (ℓ/min.)	9.8 (37.0)			
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)			
Total hydraulic flow	GPM (ℓ/min.)	14.7 (55.6)			
3-point hitch		Category I			
Lift capacity at 24 in. behind lift point	lbs. (kg)	2760 (1250)			
Traveling System					
Transmission		FST 8F/8R	GST 12F/8R	HST Plus (3 Ranges)	
Steering		Hydrostatic power steering			
Brake		Wet disc type			
Clutch		Dry type single stage			
Standard tire size *2	Front	8.3-16			
	Rear	14.9-24			

Travel speeds			GST *3		HST Plus	
No. of speeds (at rated engine speed)			12 Forward /8 Reverse			
			Forward	Reverse	Forward	Reverse
First Ninth	mph (km/h)		1.0 (1.6) 5.8 (9.4)	1.0 (1.6)	H-DS L	L: 2.2 (3.6) L: 2.0 (3.2)
Second Tenth			1.4 (2.3) 7.0 (11.3)	1.4 (2.2)		M: 4.5 (7.3) M: 4.0 (6.5)
Third Eleventh			1.9 (3.1) 11.4 (18.3)	2.2 (3.6)		H: 9.6 (15.4) H: 8.6 (13.9)
Fourth Twelfth			2.3 (3.7) 16.8 (27.0)	3.3 (5.3)		
Fifth			2.9 (4.6)	4.7 (7.6)	H-DS L	L: 3.7 (5.9) L: 3.4 (5.4)
Sixth			3.4 (5.5)	6.7 (10.8)		M: 7.5 (12.1) M: 6.8 (10.9)
Seventh			4.1 (6.6)	10.9 (17.5)		H:16.0 (25.8) H:14.4 (23.2)
Eighth			5.0 (8.0)	16.0 (25.8)		

Dimensions					
Overall length (w/o 3P)	in. (mm)	121.5 (3085)			
Overall width (min. tread)	in. (mm)	66.5 (1690)			
Overall height (w/Foldable ROPS)	in. (mm)	94.4 (2400)			90.2 (2290)
Wheelbase	in. (mm)	74.6 (1895)			
Min. ground clearance	in. (mm)	14.6 (370)			
Tread Front	(Front tire) in. (mm)	51.2 (1300)			
Rear	(Rear tire) in. (mm)	50.6 (1285) 56.5 (1435) 60.2 (1530)			
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)			
Weight (with ROPS)	lbs. (kg)	3527 (1600)	3571 (1620)	3671 (1665)	4001 (1815)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.
For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. Not for sale in Nebraska.
*1 With Master Clutch. *2 Kubota offers several tire options. *3 Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.*

Grand L40 Series

Kubota

SPECIFICATIONS

Specifications

Model		L4740		
		GST (4WD)	HST (4WD)	HSTC (4WD, CAB)
Engine				
Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel		
Engine gross power	HP (kW)	49.0 (36.6)		
Engine net power	HP (kW)	47.0 (35.1)		
PTO power	HP (kW)	41.5 (30.9)	40.0 (29.8)	
No. of cylinders / Aspiration		4 / Natural		
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)		
Total displacement	cu. in. (cc)	148.5 (2434)		
Rated speed	rpm	2700		
Battery		12V, RC: 133 min, 582A		
Alternater		12V, 45A		12V, 60A
Fuel tank capacity	US gal. (ℓ)	14.3 (54)		
PTO				
Rear PTO				
Revolution		1 speed: 540 rpm		
Type		Independent	Independent *1	
Mid PTO		Option		
Revolution		1 speed: 2000 rpm		
Hydraulic				
Lift control type: Position		Standard		
Draft		Option		
Implement pump	GPM (ℓ/min.)	9.8 (37.0)		
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)		
Total hydraulic flow	GPM (ℓ/min.)	14.7 (55.6)		
3-point hitch		Category I		
Lift capacity at 24 in. behind lift point	lbs. (kg)	2760 (1250)		
Traveling System				
Transmission		GST 12F/8R	HST Plus (3 Ranges)	
Steering		Hydrostatic power steering		
Brake		Wet disc type		
Clutch		Dry type single stage		
Standard tire size *2	Front	8.3-16		
	Rear	14.9-24		

Travel speeds

No. of speeds (at rated engine speed)			GST *3 12 Forward /8 Reverse		HST Plus		
			Forward	Reverse		Forward	Reverse
First	Ninth	mph (km/h)	0.9 (1.5)	5.5 (8.9)	0.9 (1.4)	H-DS L L: 2.2 (3.6)	L: 2.0 (3.2)
Second	Tenth		1.3 (2.1)	6.7 (10.7)	1.2 (2.0)	M: 4.5 (7.3)	M: 4.0 (6.5)
Third	Eleventh		1.8 (2.9)	10.8 (17.4)	2.1 (3.3)	H: 9.6 (15.4)	H: 8.6 (13.9)
Fourth	Twelfth		2.2 (3.5)	16.0 (25.7)	3.0 (4.9)		
Fifth			2.6 (4.2)		4.5 (7.2)	H-DS H L: 3.7 (5.9)	L: 3.4 (5.4)
Sixth			3.2 (5.1)		6.3 (10.2)	M: 7.5 (12.1)	M: 6.8 (10.9)
Seventh			3.9 (6.3)		10.3 (16.6)	H:16.0 (25.8)	H:14.4 (23.2)
Eighth			4.7 (7.6)		15.2 (24.5)		

Dimensions				
Overall length (w/o 3P)	in. (mm)	123.8 (3145)		
Overall width (min. tread)	in. (mm)	66.5 (1690)		
Overall height (w/Foldable ROPS)	in. (mm)	97.6 (2480)		93.3 (2370)
Wheelbase	in. (mm)	74.6 (1895)		
Min. ground clearance	in. (mm)	14.6 (370)		
Tread Front	(Front tire) in. (mm)	51.2 (1300)		
Rear	(Rear tire) in. (mm)	50.6 (1285) 56.5 (1435) 60.2 (1530)		
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	8.9 (2.7)		
Weight (with ROPS)	lbs. (kg)	3751 (1620)	3671 (1665)	4001 (1815)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. Not for sale in Nebraska.
**1 With Master Clutch. *2 Kubota offers several tire options. *3 Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.*

Grand L40 Series

Kubota

SPECIFICATIONS

Specifications

Model		L5040 GST (4WD)
Engine		
Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel
Engine gross power	HP (kW)	52.0 (38.9)
Engine net power	HP (kW)	50.0 (37.3)
PTO power	HP (kW)	44.0 (32.8)
No. of cylinders / Aspiration		4 / Turbo charged
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)
Total displacement	cu. in. (cc)	148.5 (2434)
Rated speed	rpm	2600
Battery		12V, RC: 133 min, 582A
Alternater		12V, 45A
Fuel tank capacity	US gal. (ℓ)	14.3 (54)
PTO		
Rear PTO		
Revolution		1 speed: 540 rpm
Type		Independent
Mid PTO		Option
Revolution		1 speed: 2000 rpm
Hydraulic		
Lift control type: Position		Standard
Draft		Option
Implement pump	GPM (ℓ/min.)	9.4 (35.6)
Power steering pump	GPM (ℓ/min.)	4.7 (17.9)
Total hydraulic flow	GPM (ℓ/min.)	14.1 (53.5)
3-point hitch		Category I & II
Lift capacity at 24 in. behind lift point	lbs. (kg)	2980 (1350)
Traveling System		
Transmission		GST 12F/8R
Steering		Hydrostatic power steering
Brake		Wet disc type
Clutch		Dry type single stage
Standard tire size[*2]	Front	9.5-16
	Rear	14.9-26
Travel speeds		GST[*3]
No. of speeds (at rated engine speed)		12 Forward /8 Reverse
		Forward / Reverse
First Ninth	mph (km/h)	0.9 (1.5) / 0.9 (1.4)
Second Tenth		1.3 (2.1) / 5.5 (8.8) / 1.2 (2.0) / 6.6 (10.6)
Third Eleventh		1.8 (2.9) / 10.8 (17.3) / 2.1 (3.3)
Fourth Twelfth		2.1 (3.4) / 15.8 (25.5) / 3.0 (4.8)
Fifth		2.6 (4.2) / 4.5 (7.2)
Sixth		3.2 (5.1) / 6.3 (10.2)
Seventh		3.9 (6.3) / 10.3 (16.5)
Eighth		4.7 (7.5) / 15.2 (24.4)
Dimensions		
Overall length (w/o 3P)	in. (mm)	126.4 (3210)
Overall width (min. tread)	in. (mm)	67.3 (1710)
Overall height (w/Foldable ROPS)	in. (mm)	98.0 (2490)
Wheelbase	in. (mm)	75.4 (1915)
Min. ground clearance	in. (mm)	15.7 (400)
Tread Front	(Front tire) in. (mm)	52.8 (1340)
Rear	(Rear tire) in. (mm)	52.2 (1325) / 56.3 (1430)
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	9.2 (2.8)
Weight (with ROPS)	lbs. (kg)	3803 (1725)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.
For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. Not for sale in Nebraska.
*[*1] With Master Clutch. [*2] Kubota offers several tire options. [*3] Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.*

Grand L40 Series

Kubota

SPECIFICATIONS

Specifications

Model		L5240	
		HST (4WD)	HSTC (4WD, CAB)
Engine			
Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel	
Engine gross power	HP (kW)	54.0 (40.3)	
Engine net power	HP (kW)	52.0 (38.8)	
PTO power	HP (kW)	45.0 (33.6)	
No. of cylinders / Aspiration		4 / Turbo with EGR	
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)	
Total displacement	cu. in. (cc)	148.5 (2434)	
Rated speed	rpm	2600	
Battery		12V, RC: 133 min, 582A	
Alternater		12V, 45A	12V, 60A
Fuel tank capacity	US gal. (ℓ)	14.3 (54)	
PTO			
Rear PTO			
Revolution		1 speed: 540 rpm	
Type		Independent*1	
Mid PTO		Option	
Revolution		1 speed: 2000 rpm	
Hydraulic			
Lift control type: Position		Standard	
Draft		Option	
Implement pump	GPM (ℓ/min.)	9.4 (35.6)	
Power steering pump	GPM (ℓ/min.)	4.7 (17.9)	
Total hydraulic flow	GPM (ℓ/min.)	14.1 (53.5)	
3-point hitch		Category I & II	
Lift capacity at 24 in. behind lift point	lbs. (kg)	2980 (1350)	
Traveling System			
Transmission		HST Plus (3 Ranges)	
Steering		Hydrostatic power steering	
Brake		Wet disc type	
Clutch		Dry type single stage	
Standard tire size*2	Front	9.5-16	
	Rear	14.9-26	
Travel speeds		HST Plus	
No. of speeds (at rated engine speed)			
		Forward / Reverse	
First Ninth	mph (km/h)	H-DS L L: 2.1 (3.4) / L: 1.9 (3.1)	
Second Tenth		M: 4.3 (7.0) / M: 3.9 (6.3)	
Third Eleventh		H: 9.3 (14.9) / H: 8.3 (13.4)	
Fourth Twelfth		H-DS H L: 3.6 (5.8) / L: 3.2 (5.2)	
Fifth		M: 7.3 (11.8) / M: 6.6 (10.6)	
Sixth		H:15.5 (24.9) / H:13.9 (22.4)	
Seventh			
Eighth			
Dimensions			
Overall length (w/o 3P)	in. (mm)	126.4 (3210)	
Overall width (min. tread)	in. (mm)	67.3 (1710)	
Overall height (w/Foldable ROPS)	in. (mm)	98.0 (2490)	94.7 (2405)
Wheelbase	in. (mm)	75.4 (1915)	
Min. ground clearance	in. (mm)	15.7 (400)	
Tread Front	(Front tire) in. (mm)	52.8 (1340)	
Rear	(Rear tire) in. (mm)	52.2 (1325) / 56.3 (1430)	
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	9.2 (2.8)	
Weight (with ROPS)	lbs. (kg)	3902 (1770)	4233 (1920)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. Not for sale in Nebraska.
**1 With Master Clutch. *2 Kubota offers several tire options. *3 Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.*

Grand L40 Series

Kubota

SPECIFICATIONS

Specifications

Model		L5740	
		HST (4WD)	HSTC (4WD, CAB)
Engine			
Type		E-TVCS, indirect injection, vertical, liquid-cooled 4-cycle diesel	
Engine gross power	HP (kW)	59.0 (44.0)	
Engine net power	HP (kW)	57.0 (42.5)	
PTO power	HP (kW)	50.0 (37.3)	
No. of cylinders / Aspiration		4 / Turbo with EGR	
Bore & stroke	in. (mm)	3.4 × 4.0 (87 × 102.4)	
Total displacement	cu. in. (cc)	148.5 (2434)	
Rated speed	rpm	2700	
Battery		12V, RC: 133 min, 582A	
Alternater		12V, 45A	12V, 60A
Fuel tank capacity	US gal. (ℓ)	14.3 (54)	
PTO			
Rear PTO			
Revolution		1 speed: 540 rpm	
Type		Independent*1	
Mid PTO		Option	
Revolution		1 speed: 2000 rpm	
Hydraulic			
Lift control type: Position		Standard	
Draft		Option	
Implement pump	GPM (ℓ/min.)	9.8 (37.0)	
Power steering pump	GPM (ℓ/min.)	4.9 (18.6)	
Total hydraulic flow	GPM (ℓ/min.)	14.7 (55.6)	
3-point hitch		Category I & II	
Lift capacity at 24 in. behind lift point	lbs. (kg)	2976 (1350)	
Traveling System			
Transmission		HST Plus (3 Ranges)	
Steering		Hydrostatic power steering	
Brake		Wet disc type	
Clutch		Dry type single stage	
Standard tire size*2	Front	9.5-16	
	Rear	14.9-26	
Travel speeds		HST Plus	
No. of speeds (at rated engine speed)			
First Ninth Second Tenth Third Eleventh Fourth Twelfth Fifth Sixth Seventh Eighth	mph (km/h)	Forward / Reverse H-DS L L: 2.2 (3.6) / L: 2.0 (3.2) M: 4.5 (7.3) / M: 4.1 (6.6) H: 9.6 (15.5) / H: 8.6 (13.9) H-DS H L: 3.7 (6.0) / L: 3.4 (5.4) M: 7.6 (12.2) / M: 6.8 (11.0) H:16.1 (25.9) / H:14.5 (23.3)	
Dimensions			
Overall length (w/o 3P)	in. (mm)	126.4 (3210)	
Overall width (min. tread)	in. (mm)	67.3 (1710)	
Overall height (w/Foldable ROPS or CAB)	in. (mm)	101.0 (2565)	94.7 (2405)
Overall height (w/Foldable ROPS (-2 model))	in. (mm)	98.0 (2490)	–
Wheelbase	in. (mm)	75.4 (1915)	
Min. ground clearance	in. (mm)	15.7 (400)	
Tread Front	(Front tire) in. (mm)	52.8 (1340)	
Rear	(Rear tire) in. (mm)	52.2 (1325) 56.3 (1430)	
Min. turning radius (w/brake, 4WD disengaged)	feet (m)	9.2 (2.8)	
Weight (with ROPS)	lbs. (kg)	3902 (1770)	4233 (1920)

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information.
For your safety, KUBOTA strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. Not for sale in Nebraska.
*1 With Master Clutch. *2 Kubota offers several tire options. *3 Speeds 3,5,7 and 9 of the GST are not included in the FST's 8 forward speeds.*